

OVERVIEW

Duratherm LT heat transfer fluid is engineered for applications requiring process temperatures ranging from -30°F to 600°F.

Ideal for batch processing requiring heating and cooling cycles. Eliminates the need for heat tracing in outdoor applications.

APPLICATION

Duratherm LT is an oxidative and thermally stable, high performance, long lasting, environmentally friendly heat transfer fluid. Offering precise temperature control between -30°F and 600°F. **Duratherm LT** engineered for applications requiring process temperatures ranging from -30°F to 600°F.

Ideal for batch processing requiring heating and cooling cycles. Eliminates the need for heat tracing in outdoor applications.

THE DIFFERENCE

Our exclusive additive package, including a proprietary dual stage anti-oxidant, ensures long trouble-free operation. Duratherm also incorporates metal deactivators, a seal and gasket extender, de foaming and particle suspension agents.

LASTS LONGER

In the heat transfer fluid industry cost is always a concern, however fluid longevity and resistance to harmful fouling are of equal importance.

Air contact is normally detrimental to a fluid. Oxidation can cripple your system and if left unchecked will ultimately cause catastrophic failure. Unscheduled downtime due to oil failure has a high cost and negative effect on production.

The Duratherm product line was developed with this in mind. Most other fluids fall short in their protection from oxidation and can quickly foul a system. Duratherm is engineered to give unsurpassed levels of protection and service life.

ENVIRONMENTAL

Duratherm LT heat transfer fluid is environmentally friendly, non-toxic, non-hazardous and non-reportable. Worker health and safety is of great concern, **Duratherm LT** heat transfer fluid poses no ill effect to worker safety. After its long service life it can easily be disposed of with other waste oils.

DURATHERM LT PROPERTIES

| | | |
|---|--------------------|----------------|
| Appearance: colorless, clear and bright liquid | | |
| Maximum Bulk/Use Temp.* | 600°F | 315°C |
| Flash Point ASTM D92 | 329°F | 165°C |
| Fire Point ASTM D92 | 370°F | 188°C |
| Autoignition ASTM E-659-78 | 675°F | 357°C |
| Viscosity ASTM D445 | | |
| cSt at 104°F / 40°C | 7.9 | |
| cSt at 212°F / 100°C | 2.3 | |
| cSt at 600°F / 316°C | 0.5 | |
| Pour Point ASTM D97 | -72°F | -58°C |
| Density ASTM D1298 | lb/ft3 | g/ml |
| at 100°F / 38°C | 50.1 | 0.802 |
| at 500°F / 260°C | 40.4 | 0.65 |
| at 600°F / 316°C | 38.9 | 0.623 |
| Average Molecular Weight | 395 | |
| Carbon Residue ASTM D189 | 0.005 | % Mass |
| Sulphur Content X-RAY | <.001 | weight % |
| CU Strip Corrosion ASTM D130 | 1a | |
| Thermal Expansion Coefficient | 0.0564 %/°F | 0.1011 %/°C |
| Thermal Conductivity | BTU/hr F ft | W/m.K |
| at 100°F / 38°C | 0.081 | 0.140 |
| at 500°F / 260°C | 0.070 | 0.121 |
| at 600°F / 316°C | 0.066 | 0.114 |
| Heat Capacity | BTU/lb F | kJ/kg K |
| at 100°F / 38°C | 0.511 | 2.139 |
| at 500°F / 260°C | 0.691 | 2.914 |
| at 600°F / 316°C | 0.723 | 3.027 |
| Vapor Pressure ASTM D2879 | psia | kPa |
| at 100°F / 38°C | 0.00 | 0.00 |
| at 500°F / 260°C | 4.19 | 28.88 |
| at 600°F / 316°C | 8.05 | 55.50 |
| Distillation Range ASTM D2887 | 10% | 613°F (323°C) |
| | 90% | 784°F (418°C) |
| *Maximum Film Temp. | 630°F | 332°C |

The values quoted are typical of normal production. They do not constitute a specification.